

Effective and stylish, SERIFLEX® meets all Movable Wall requirements within a controlled budget, ideal for restaurant dining rooms, play areas and quiet rooms in daycares and nursery schools, cafeterias...

PRINCIPLE

Custom-made acoustic movable wall system. Sliding panels in a top track without any floor guidance.

ACOUSTIC

The SERIFLEX 41° offers an acoustic reduction Rw of 41 dB.

SILENT AND EASY TO MOVE

ALGAFLEX® assures an exclusive system: Polymer-coated, self-lubricating, wear-resistant ball bearing trolleys (Delrin).

TECHNICAL RELIABILITY

Our SERIFLEX 41® walls have undergone the most rigorous endurance and mechanical resistance tests, in a specific lab or in ALGAFLEX's own Test Center.
5-year parts and labor warranty

IMPLEMENTATION

Panels can be fixed by a central suspension (MONODIRECTIONAL) composed of 4 self-lubricating and highly resistant polymer rollers ensuring a smooth and silent movement without friction.

Panels can also be fixed by 2 trolleys (MULTI DIRECTIONAL) with self-lubricating polymer rollers with double direction of rotation ensuring smooth and silent movement without friction.


QUICK TO INSTALL

Top and bottom telescopic seals are locked in place with just 1/3 of a turn of a removable handle.

FACE FINISH

Melamine 12 mm range ALGAFLEX® white and grey.

JOINING PANELS







	Panel Maximum Width	Custom made according to finishing
<u>•</u>	Weight starting from *	29 Kg /m²
I	Panel Maximum Height	3 000 mm
(((Sound Reduction	Rw 41 dB / Ra 39 dB
▶◀	Thickness	100 mm
6	Fire Reaction	Meets standard AM14

- * Weight for panels of 3000 x 1200 mm
- * Depending on the specificities of the project, our design office will adapt the measurements.